









# THERMOSTATS CABLE CONTROLLED

	DESCRIPTION	DTAC NO.
	Cable Controlled 19 1/2" Capillary  404077	03-14009
	Cable Controlled 19" Capillary Mounting Hole Spacing 3"  404088	03-14010
	Cable Controlled 43" Capillary Push for Cold Mounting Hole Spacing 2 15/16"  71R2800	03-14012
	Cable Controlled 18" Capillary Mounting Hole Spacing 2 3/16"  71R2600	03-14018

NOTES \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

# THERMOSTATS ROTARY



	DESCRIPTION	DTAC NO.
	Rotary Thermostat Variable Temperature 18" Capillary	<b>03-14001</b>
	Rotary Thermostat Variable Temperature 24" Capillary	<b>03-14002</b>
	Rotary Thermostat Variable Temperature 48" Capillary	<b>03-14003</b>
	Rotary Thermostat Variable Temperature 49" Capillary	<b>03-14004</b>  71R2310
	Rotary Thermostat Variable Temperature 18" Capillary	<b>03-14008</b>  404002
	Rotary Thermostat 66" Capillary	<b>03-14016</b>  71R2400

